

## AREAS OF USE

### CERMIX TILE ADHESIVES PRODUCT RECOMMENDATION TABLE

		CERMICOL EXTRA	CERMICOL SUPER	CERMI FLEX	CERMIGRES	CERMIGRANT	CERMIPLUS	CERMIPOOL	CERMIPLUS RAPID	CERMIPLUS XL	CERMI F I X HP	CERMI F I X PU 2C
TILE FORMAT	Ceramic Tile, Glass Mosaic, Marble, Natural Stone etc	≤ 1.600 cm <sup>2</sup> (40x40 cm)	≤ 1.600 cm <sup>2</sup> (40x40 cm)	≤ 3.600 cm <sup>2</sup> (60x60 cm)	“≤ 3.600 cm <sup>2</sup> (60x60 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 14.400 cm <sup>2</sup> (120x120 cm)” (****)	“≤ 3.600 cm <sup>2</sup> (60x60 cm)”	“≤ 14.400 cm <sup>2</sup> (120x120 cm)” (****)
	Porcelain Tile, Granite Tile, Cotto, Clinker etc			≤ 3.600 cm <sup>2</sup> (60x60 cm)	“≤ 3.600 cm <sup>2</sup> (60x60 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 7.200 cm <sup>2</sup> (60x120 cm)”	“≤ 14.400 cm <sup>2</sup> (120x120 cm)” (****)	“≤ 3.600 cm <sup>2</sup> (60x60 cm)”	“≤ 14.400 cm <sup>2</sup> (120x120 cm)” (****)
APPLICATION SURFACE	Cement Based Plaster, Screed, Concrete etc	●	●	●	●	●	●	●	●	●	●	
	Gypsum Plaster, Pannel (*)		●	●	●	●	●		●		●	
	Existing Tile (**)		●	●	●	●	●	●	●	●	●	
	Painting		●	●	●	●	●		●		●	
	Wood, Metal etc											●
APPLICATION AREA	Interior	●	●	●	●	●	●		●		●	●
	Exterior			●	●	●	●	●	●	●		●
	Floor Heating System, Terrace, Cold Storage					●	●			●		
	Floors Exposed to Heavy Foot Traffic (Hospital, Shopping Center etc)					●	●			●		●
	Pool, Turkish Bath, Water Tank						●	●		●		
	Exterior Tiling of Ceramic (***)									●		
	Rapid Tiling of Places (Bank, Cafe, Supermarket etc)								●			

(\*) Surface should be primed with CERMIFILM before cementitious product applications.

(\*\*) Surface should be primed with CERMIFILM PLUS / CERMIFILM PLUS RAPID before cementitious product applications.

(\*\*\*) Surface should be primed with CERMIFILM. Application should be applied with combined bonding method, up to 10 m height, max sized 60x60 cm ceramic. Please contact Koramic Technical Service for more information.

(\*\*\*\*) Please contact Koramic Technical Services Department for different sized ceramic tile applications.

● Suitable for use.